


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



PART DESCRIPTION			
STEEL BODY NSV - EXPLODED			
MATERIAL			
MATERIAL			
DRAWN BY		APPROVAL	
KWK		MLZ	
SIZE	FSCM NO.	DWG NO.	REV
B		310 401XXSNSV	B
SCALE		SHEET	
1" = 2.5"		1 OF 2	

THIS DRAWING, INFORMATION, AND TECHNICAL DATA CONTAINED WITHIN ARE THE EXCLUSIVE PROPERTY OF INTEGRA RACING SHOCKS AND SHALL BE RETURNED UPON REQUEST. THIS DRAWING IS NOT TO BE REPRODUCED IN WHOLE OR IN PART, NOR SHALL ANY INFORMATION OR TECHNICAL DATA BE SUPPLIED, IN ANY FORM, TO ANYONE ELSE WITHOUT THE EXPRESS WRITTEN CONSENT OF INTEGRA RACING SHOCKS

BREAK EDGES .010 +/- 0.005" X 45°, FILLET RADII 0.010" +/- 0.005"  
 TOLERANCES (UOS): .XX +/- .01", .XXX +/- .003", ANG +/- 0.5°  
 ALL SURFACE FINISHES TO BE Ra 64 OR BETTER UNLESS OTHERWISE SPECIFIED.



Item Number	Quantity	Part Number	Part Name
1	1	310 30211	Rod Guide O-ring, Primary
2	2	SEE BLOW UP	Disc Stack, Standard
3	1	310 30215	Piston Band Energizing O-Ring
4	1	310 30233	NSV Floating Piston, Assembly - Includes (1)4, (1)7, (1)11, (1)12, (1)24
5	2	310 30281	Seal - Low Friction_B
6	1	310 30281	Seal - Low Friction_A
7	1	310 30257	Retaining Ring - NSV Floating Piston
8	1	310 30322/30323/30325	Piston, Digressive/Linear/Linear-Digressive
9	1	310 30217	Piston Washer
10	1	310 30224	Steel Rod End, Assembly - Includes (1)16, (1)25
11	1	310 43235-2.1	NSV Valve Pressure Disc
12	1	310 30256	Ball, Fill - NSV
13	1	310 30441	Steel NSV End Cap, Assembly - Includes (1)16, (1)25
14	1	310 30280	Wiper - Low Friction
15	1	310 30210	Rod Guide O-ring, Secondary
16	2	310 30328	Retaining Ring, Spherical Bearing
17	1	310 30216	Piston Nut
18	2	310 30335	Standard Disc Travel Limiter
19	1	310 30213	Floating Piston O-ring
20	1	310 30226	Steel Rod Guide, Assembly - Includes (1)1, (2)5, (1)6, (1)14, (1)15, (1)30
21	1	310 30218	Travel Marker
22	1	310 30214	Piston Band
23	1	310 3044X	Steel Pressure Tube (Specify Length)
24	1	310 30413	Self Sealing Screw
25	2	310 30327	Spherical Bearing
26	1	310 30350	Floating Piston Retaining Ring
27	1	310 30439	New Style Steel End Cap Seal
28	1	310 30338	7/16" x 11/16" Jam Nut
29	1	310 3031X	Standard Piston Rod (Specify Length)
30	1	310 30300-1	Rod Guide DU Bearing
31	1	310 BD0XX-X	Bleed Disc (Specify Thickness and Bleed)
32	1	310 MVD594020	Backup Disc/Torque Washer
33	1	310 MVD70XX	.700" DIA Main Valve Disc (Specify Thickness)
34	1	310 MVD850XX	.850" DIA Main Valve Disc (Specify Thickness)
35	1	310 MVD10XX	1.00" DIA Main Valve Disc (Specify Thickness)
36	1	310 MVD1160XX	1.16" DIA Main Valve Disc (Specify Thickness)
37	1	310 MVD1280XX	1.28" DIA Main Valve Disc (Specify Thickness)
38	1	310 PR1280XX	Preload Ring Disc (Specify Thickness)

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

A	RELEASED		22 MAR 2010	
B	UPDATED END CAP PART # UPDATED PRESSURE TUBE PART # CREATED 3D MODEL		7 JULY 2011	

PART DESCRIPTION			
STEEL NSV - PARTS LIST			
MATERIAL			
MATERIAL			
DRAWN BY		APPROVAL	
KWK		MLZ	
SIZE	FSCM NO.	DWG NO.	REV
B		310 401XXSNSV	B
SCALE		SHEET 2 OF 2	

THIS DRAWING, INFORMATION, AND TECHNICAL DATA CONTAINED WITHIN ARE THE EXCLUSIVE PROPERTY OF INTEGRA RACING SHOCKS AND SHALL BE RETURNED UPON REQUEST. THIS DRAWING IS NOT TO BE REPRODUCED IN WHOLE OR IN PART, NOR SHALL ANY INFORMATION OR TECHNICAL DATA BE SUPPLIED, IN ANY FORM, TO ANYONE ELSE WITHOUT THE EXPRESS WRITTEN CONSENT OF INTEGRA RACING SHOCKS

BREAK EDGES .010 +/- 0.005" X 45°, FILLET RADII 0.010" +/- 0.005" TOLERANCES (UOS): .XX +/- .01", .XXX +/- .003", ANG +/- 0.5° ALL SURFACE FINISHES TO BE Ra 64 OR BETTER UNLESS OTHERWISE SPECIFIED.